



The information in this document is proprietary and confidential to Rolls-Royce and is available to authorised recipients only – copying and onward distribution is prohibited other than for the purpose for which it was made available

REDUCED INSPECTION USING PROBABILISTIC ANALYSIS

ISPMNA5, Tokyo, October 7 – 9, 2024

Rob Marshall, Technical Specialist – Structural Integrity

Mike Martin, Engineering Fellow – Structural Integrity

Ruben Virumbrales Bell, Manufacturing Engineer

October 9, 2024

UA5



Agenda

01 Background / Extant Position

02 Method

03 Improved Position





01

Background / Extant Position



Extant Position


- Pressure retaining pipe sections butt welded
- Internal surface defects contribute to structural failure and reduce thermal hydraulics performance
- 100% inspection conducted
- Any defects detected measured
- Compared against deterministic limit
 - Accept, rework or concession based on bespoke assessment
 - Historically 99.9%+ of measured features accepted against deterministic limit
- Further downstream manufacturing processes conducted but not accounted for





Manufacturing Route


- Inserts added prior to welding
 - Opportunities to scratch internal surfaces





Manufacturing Route


- Inserts added prior to welding
 - Opportunities to scratch internal surfaces
- Spatter during autogenous welding







Manufacturing Route

- Inserts added prior to welding
 - Opportunities to scratch internal surfaces
- Spatter during autogenous welding
- Inserts removed



Manufacturing Route


- Inserts added prior to welding
 - Opportunities to scratch internal surfaces
- Spatter during autogenous welding
- Inserts removed
- Polymer replicant used to find defects
 - Inserted into pipe
 - Removed using bespoke tooling
 - Visual inspected for defects
 - All detected defects laser scanned for dimensions
 - Method can result in damage
 - Tooling required to remove polymer
 - Human factors influence on detection





Manufacturing Route

- Inserts added prior to welding
 - Opportunities to scratch internal surfaces
- Spatter during autogenous welding
- Inserts removed
- Polymer replicant used to find defects
 - Inserted into pipe
 - Removed using bespoke tooling
 - Visual inspected for defects
 - All detected defects laser scanned for dimensions
 - Method can result in damage
 - Tooling required to remove polymer
 - Human factors influence on detection
- Reworks conducted as required
 - Reinspection conducted post repair






02

Method



Data-Centric Engineering






V&V Validation and Verification
NDE Non Destructive Examination
SHM Structural Health Monitoring
EHM Equipment Health Monitoring
ISI In-Service Inspection

- Holistic use of lifecycle data from raw material and manufacture through to operation, maintenance and decommissioning
- Product and fleet digital twins of degradation mechanisms
- Uncertainty quantification and probabilistics
- Integrated physics-based multiscale models
- Surrogate and reduced order approaches

Data Centric Engineering Approach

- Statistical view on defect generation
 - Review of manufacturing processes
 - Trial Data
 - Downstream processing
 - Similar products







Data Centric Engineering Approach



- Statistical view on defect generation
 - Review of manufacturing processes
 - Trial Data
 - Downstream processing
 - Similar products
- Review of current measurement capability
 - Likelihood of false positives
 - Reliability of missing defects

Inspector ID	Defect ID				
	A	B	C	D	E
1	✓	x	x	✓	✓
2	✓	✓	x	✓	✓
3	x	✓	x	✓	x





Data Centric Engineering Approach

- Statistical view on defect generation
 - Review of manufacturing processes
 - Trial Data
 - Downstream processing
 - Similar products
- Review of current measurement capability
 - Likelihood of false positives
 - Reliability of missing defects
- Statistical view on loading
 - As-built data
 - Quantification of reliability required



Data Centric Engineering Approach

- Statistical view on defect generation
 - Review of manufacturing processes
 - Trial Data
 - Downstream processing
 - Similar products
- Review of current measurement capability
 - Likelihood of false positives
 - Reliability of missing defects
- Statistical view on loading
 - As-built data
 - Quantification of reliability required
- Combined assessment
 - Understand true worth of the inspection method







03

Improved Position



Improved Position

- Statistical view on defect generation
 - Structurally significant defects highly unlikely
 - Process understanding conducted to prevent damage
- Review of current measurement capability
 - Capability limited
- Statistical view on loading
 - Deterministic assessment reliability quantified
 - Variation across component understood
- Combined assessment
 - Likelihood of failure acceptable without inspection
 - Inspection shown to not significantly improve reliability
 - Significant time and cost saving implemented
- Collaboration across disciplines key to outcome





Thank you for your attention!

robert.marshall3@rolls-royce.com